ITC

Start up protocol

Please note: this is a very basic handout to give the user a "jump start" while setting the experiment. There is an extra copy of the complete manuals for ITC and ThermoVac that can be borrowed from the Biophysical Resource for limited time to produce additional copies; alternatively, the entire manual can be downloaded from:

http://info.med.yale.edu/wmkeck/biophysics/VP_ITC_MANUAL_11_20_02a.pdf (follow the link from the main ITC page).

Each user is strongly advised to read the full manual before operating the ITC instrument independently.

- 1. Turn on power on VP-ITC (back of the instrument).
- 2. Launch the VPViewer 2000 ITC (double click on the VPViewer2000 ITC.Ink icon).
- 3. The following window appear:



- 4. Click OK.
- 5. The following window appears:

VPViewer2000 - Defa	ılt User						
pad Run File Save	Run File Display Run F	Param. Update Rur	Param.	Star	,	STOP Stop	Compact Mod
System Ir Temp (°C) 27.5	itiation - Please Wa - DP (µCal/s)	it DT (°C) 0.034					
ITC Controls	Thermos	stat/Calib.	Setu	p / Mainte	enance	Υ <u> </u>	Constants
		ITC Co	ntrols			_	
Ex	perimental Parameters —				Injection I	arameters	
Total # Injections		40	Volum	e (µl)			3.006
Cell Temperature	(*C.)	30	Durati	on (sec.)			6
Reference Power	(µCal/sec.) (1 - 34.2)	5	Spaci	ng (sec.)			210
Initial Delay (sec.	1	60	Filter	Period (se	 c.)		2
Syringe Concentr.	ation (mM)	0			Edit	Mode	
Cell Concentration	n (mM)	0	\$ A	ll Same	🔷 Uniqu	e 🔷 Al	oply To Rest
Stirring Speed		290 💌		Volume	Duration	Spacing	Filter
Data File Name			1	3.0	6.0	210	2
	default.itc		2	3.0	6.0 6.0	210	2
None	eedback Mode/Gain —	🐟 Hiah	4	3.0	6.0	210	2
	V	·	5	3.0	6.0	210	2
	C Equilibration Options					iit	
No Lneck Ten	ip Fast Equil.	Auto			1	m	1
	Data File Comments					Ţ1	
		<u> </u>		oen Fill Po	irt _	Purge->R	eFill
				<u> </u>		D. 1	<u>U</u> p
		T	CI	ose Fill Pa	ort [)istance (in	<u>D</u> n
1							

- 6. This window illustrates most of the parameters that define how the ITC experiment will be performed. The parameters are loaded from the recently used file, so they might be quite different than the ones that a given user had used previously. *During your training session a "default" experiment will be created for you and saved in your directory,* so you can load your settings by choosing "Load run setup file" (top left corner- first button).
- 7. The following window appear:

Load Run Param	eters			<u>?</u> ×
Look jn:	🗀 Setup	•	+ 🗈 💣 🎟 -	
My Recent Documents Desktop My Documents My Computer	Isstrun1.inj METHANOL.INJ RNASE.INJ WATER.INJ WATER_ewa.inj			
My Network Places	File name: Files of type: Setup Files (".ini)		•	<u>O</u> pen Cancel

- 8. Find your directory and load appropriate settings.
- 9. The following window appears:

yseen pro gep Wield Run File Save Run File Display Run Param. Update Run Param. Start Stop Final Baseline Equilibration Temp (°C) DP (µCal's) 0.000 ITC Controls Thermostat/Calib. Setup / Maintenance Constants ITC Controls Injection Parameters Injection Parameters Injection Parameters Volume [µl] 3 Duration (sec.) 6 Spacing (sec.) [1 - 34.2) 5 Initial Delay (sec.) [1 - 34.2) 5 Initial Delay (sec.) [1 - 34.2) 5 Suring Speed 290 v Data File Name Rnase112402414pm.itc Feedback Mode/Gain No Check Temp. Fast Equil Auto Available Titrant 275.19 µl Ready					
Final Baseline Equilibration Temp (°C) DP (µCal/s) DT (°C) 30.0 4.401 0.000 Internostat/Calib. Setup / Maintenance Constants Injection Parameters Injection Parameters Volume (µl) 3 Data #ile Name Rnase112402414pm.itc Volume Quartion Spacing Filter 1 3.0 6.0 210 2 2 3.0 6.0 210 2 2 3.0 6.0 210 2 2 3.0 6.0 210 2 3 0 6.0 210 2 3 3.0 6.0 210 2 3 3.0 6.0 210 2 3 0 6.0 210 2 3 0 6.0 210 2 3 0 6.0 210 2 3 0 6.0 210 <t< th=""><th>Param. Update Run Param. Start Stop</th><th>► ■► Compact Mode</th></t<>	Param. Update Run Param. Start Stop	► ■► Compact Mode			
ITC Controls Thermostat/Calib. Setup / Maintenance Constants ITC Controls ITC Controls Injection Parameters Total # Injections 40 Cell Temperature (°C.) 30 Reference Power (µCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560! Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options ♦ Auto No Check Temp. Fast Equil. Z75.19 µl ITC and E Titrant Z75.19 µl ITC and another itrant)T (°C)).000				
ITC Controls Experimental Parameters Injection Parameters Total # Injections 40 Cell Temperature (°C.) 30 Reference Power (µCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options ♦ High ITC Equilibration Options ♦ Auto Available Titrant 275.19 µl Z75.19 µl Image: Fill Pott Image: Fill Pott Distance (in.) Dn	tat/Calib. Setup / Maintenance Cons	nstants			
Experimental Parameters Injection Parameters Total # Injections 40 Cell Temperature (*C.) 30 Reference Power (µCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560! Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options Auto No Check Temp. Fast Equil. Z75.19 µl Image: Fill Port Z75.19 µl Image: Fill Port Distance (in.) Image: Fill Port	ITC Controls				
Total # Injections 40 Cell Temperature (°C.) 30 Reference Power (μCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options Auto No Check Temp. Fast Equil. Available Titrant 275.19 µl Z75.19 µl Image: String Port	Injection Parameters				
Cell Temperature (*C.) 30 Reference Power (µCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options ♦ Auto Available Titrant 275.19 µl Z75.19 µl Image: Sec. Processing File Port Distance (in.) Dn	40 Volume (μl)	3			
Reference Power (μCal/sec.) [1 - 34.2) 5 Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options ▲ Auto Available Titrant 275.19 μl Z75.19 μl Image: Start Content of the start of th	30 Duration (sec.)	6			
Initial Delay (sec.) 60 Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ Low None ↓ Low ITC Equilibration Options ▲ Auto Available Titrant 275.19 µl Q75.19 µl □	5 Spacing (sec.)	210			
Initial Delay (set.) O Syringe Concentration (mM) 2.74 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ High ITC Equilibration Options I 3.0 No Check Temp. Fast Equil. Available Titrant Image: Fill Pot Image: Fill Pot Image: Fill Pot Distance (in.) Image: Fill Pot	60 Filter Period (see)	2			
Syringe Concentration (mM) 274 Cell Concentration (mM) 0.0560t Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ None ♦ Low ♦ High ITC Equilibration Options No Check Temp. Fast Equil. ▲ Auto Available Titrant 275.19 µl ↓ Colume Duration Spacing Filter 1 3.0 6.0 210 2 3 3.0 6.0 210 2 5 3.0 6.0 210 2 Feedback Mode/Gain 0.1 ↓ P Close Fill Port ↓ Colume Duration Spacing Filter 1 3.0 6.0 210 2 5 3.0 6.0 210 2 Column Duration Spacing Filter 1 3.0 6.0 210 2 Column Duration Spacing Filter 2 3.0 6.0 210 2 Column Duration Spacing Filter 2 3.0 6.0 210 2 Column Duration Spacing Filter 2 4 3.0 6.0 210 2 Column Duration Spacing Filter 2 5 3.0 6.0 210 2 Column Duration Spacing Filter 2 5 5 3.0 6.0 210 2 Column Duration Spacing Filter 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5					
Cell Concentration (mM) [0.0560] Stirring Speed [290] ▼ Data File Name Rnase112402414pm.itc Feedback Mode/Gain 1 ♦ None ♦ Low ITC Equilibration Options ▲ Auto Available Titrant Øpen Fill Port Image: Construction options Image: Construction options Image: Co	Edit Mode	To Post			
Stirring Speed 290 ▼ Data File Name Rnase112402414pm.itc Peedback Mode/Gain 1 ♦ None ♦ Low ITC Equilibration Options ✓ Auto Available Titrant ✓ Auto 275.19 μl ✓ Itration Øret Itration		Toffest			
Data File Name Rnase112402414pm.itc Feedback Mode/Gain ♦ None ♦ Low ♦ High ITC Equilibration Options No Check Temp. Fast Equil. ♥ Auto Available Titrant 275.19 µl 0.1 Up Close Fill Port Distance (in.) Dn	290 💌 Volume Duration Spacing Fil	Filter 🔺			
Data The Name Hnase112402414pm.ttc Feedback Mode/Gain 2 ♦ None Low ITC Equilibration Options 8 No Check Temp. Fast Equil. Participation Options Pauto Available Titrant 9 275.19 μl 0.1 Uppen Fill Port 0.1 Uppen Fill Port Distance (in.)	1 3.0 6.0 210	2			
Feedback Mode/Gain ↓	m.itc 2 3.0 6.0 210	2			
ITC Equilibration Options 5 3.0 6.0 210 2 ITC Equilibration Options Image: Constraint options Image: Constraint options Ready Available Titrant Image: Constraint options Image: Constraint options Image: Constraint options 275.19 µl Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options Image: Constraint options	A ULA 4 3.0 6.0 210	2			
ITC Equilibration Options No Check Temp. Fast Equil. ☑ Auto Available Titrant ☑ Open Fill Port ☑ Up 275.19 μl	Tigh 5 3.0 6.0 210	2 💌			
Available Titrant Image: Close Fill Port Image: Close Fill Port	ITC Equilibration Options INo Check Temp. Fast Equil. Auto				
275.19 μl Dpen Fill Port Purge->ReFill 					
Image: Close Fill Port 0.1 Up Distance (in.) Dn	Open Fill Port Purge->ReFill				
	Close Fill Port	Up Dn			

- 10. The experimental setting could be modified at this time. Please update the file name ("ITC Control" Tab, Data File Name) and the path for data storage to be sure that the data file will be saved in your directory ("Set Up/Maintenance" Tab, Data File Path). Check the concentrations to be sure they reflect the currently performed titration. *NOTE*: the experimental settings can also be modified during the execution of the titration; for example, a slow progress of binding might justify increasing the injection volume. To implement a newly modified settings when the titration is in progress choose: Update Run Param.
- 11. Most commonly, the FeedBack Mode/Gain will be set at "High", ITC Equilibrium Option will be set at "Auto" and the Stirring Speed will be 290 (chosen from the pull down menu).
- 12. Update the Injection Parameters. *NOTE*: the injection could be all identical, or the injection volume, speed et.c. can be set uniquely for each injection.

CAUTION: double-check that the reference cell is filled with degassed water, the ITC cell is filled with macromolecule solution and that the Auto-Pipette is loaded, *disconnected from the filling syringe* and has been purged.

- 13. If the sample cell and syringe are ready, you may start the run by clicking the "START" bottom.
- 14. The following window appears, which is a real time display of progress of ITC titration.



15. The status of the ITC cell will change from "Heating/Cooling Jacket/Cell" to "PreRun Thermostat", "PreStirring Equilibration", "Final Baseline Equilibration" and eventually "Running" as illustrated below.





Microcal Origin - C:\Origin50\VPITC	PLOT.OPJ - [Plot1]							_ <u>8</u> ×
Elle Edit Yew Graph Data Anal	ysis <u>t</u> ools ⊨ormat <u>wi</u> ndow ≚i⇔al⇔ali⊐il⊒i ¥anei⊿as							그리스
	0							
	Current	Status			Final Base	line Equilit	bration	
Main Display	Current	otatas .		_	T Intel Dase		Station	
Temp (° C) 30.0	PP 10	1		Rn	ase112402414	lpm.itc		
DP(uCal/sec.) 4.439	9-	1						
DT (° C) 0.000	7 -							
	6 -							
	5							
	3 -							
Display Mode	2 - 9 1 -							
Rescale To Show All								
DB Casta Castala	-2							
Auto-View 1	-4 -							
	-5							
Auto-View 2	-7 -							
Saved View 1	-8 -							
Saved View 2	-10		-, -, -, -, -, -, -, -, -, -, -, -, -, -		,]	
	Ó I	200	400	600	800	1000	1200	
Edit ranges	<u>∼∕e</u>			Time (sec.)				
x = ?, y = ?								
Ŷ							Data1_DP Plot1*	NUM

stirring begins

🗱 Microcal Origin - C:\OriginSO\VPITCPLO	JT.OPJ - [Plot1]					_ & ×
Ele Edit Yew Graph Data Analysis	Tools Format Window	Help				_ 8 ×
	56888 18	MB 👗				
X 🗠 📾						
	1					
1 2 3	Current S	tatus:		Final Baseline Equili	bration	
Main Display		1				
Temp (* C) 30.0	10		Rhas	se112402414pm.itc		
DP(uCal/sec.) 4,233	"E	1				
DT 0.0	8 -	1				
0.000	7 -	1				
	6	1				
	2					
	33					
	2 2					
Display Mode	85 1 T					
Records To Show All	ÿ ! -					
Negotine to show set						
	-3 -					
	-4 -]					
ALCO VIEW 1	-5					
Auto-View 2	-6 -					
Constant and	-8 -					
Saved View 1	-9 -					
Saved View 2	-10 -10					
	0	200 400	600	800 1000	1200	
Edit ranges	Č		Time (sec.)			
RQ+BX0TZ0Z						
x = ?, y = ?						
Y					Data1_DP Plot1*	NUM

stirring continues

Microcal Origin - C:\Origin50\VPT	TCPLOT.OPJ - (Plot1)		X
	10		
123	Current Status :	ITC Pre-Titration Delay, 275,19 ul Available	
Main Display	DP	Roase112402414nm itc	
Temp (° C) 30.0		nuase i renozni replitute	
DP(uCal/sec.) 4.406	40		
DT (° C) 0.000	4.0		
	-		
	4.6 -		
	2		
Display Mode	lised		
Rescale To Show All	0 4.4 -		
	6 _		
OP Scale Controls	42		
Auto-View 1	4.2		
Auto-View 2	-		
Saveri View 1	4.0 -		
Saved View 2	0 200 4	00 600 800 1000 1200	
Edit ranges	~~e	Time (sec.)	
RQ+BLOTZO	1/00		
x = ?, y = ?			
i=2		Data1_DP Plot1*	NUM

👹 Microcal Origin - C:\Origin50\¥PITC	PLOT.OPJ - [Plot1]		_ 8 ×
🤶 Eile Edit Yiew Graph Data Anal	ysis <u>T</u> ools Format <u>W</u> indow <u>H</u> elp		_ 8 ×
	1660 B 160 		
X 🗈 🛍			
	•		
1 2 3	Current Status :	ITC Pre-Titration Delay, 275.19 µl Available	
Main Display	DP	Rnase112402414nm itc	
Temp (° C) 30.0	2	Tritase in 24024 rapinite	
DP(uCal/sec.) 4.406			
DT (° C) 0.000	4.8 -		
	_		
	4.6 —		
Display Mode	asj		
	g 4.4		
Rescale to show All	Ă		
DP Scale Controls			
Auto-View 1	4.2 -		
Auto-View 2	1		
Saved View 1	4.0 —		
Saved view 2	0 200 400	600 800 1000 1200	
Edit ranges	~∕∕∕	Time (sec.)	
x = ?, y = ?			
i=2		Data1_DP Plot1*	NUM

initial injection

Microcal Origin - C:\Origin50\VPIT	CPLOT.OPJ - [Plot1]						_ 8 ×
Eile Edit View Graph Data Ana	alysis <u>T</u> ools F <u>o</u> rmat <u>W</u> indow <u>H</u> elp						
		*					
X 🖻 🛍							
	•						
1 2 3	Current Status :		IT	C Injection #	≇1, 272.18 u	ul Available	
Main Display	DP		Rnz	ase112402414	om itc		
Temp (° C) 30.0	г						
DP(uCal/sec.) 0.985							
DT (° C) 0.000	4.8 -						
	-						
	10						
	4.6 -						
	(; ;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;						
Display Mode	S III						
Rescale To Show All							
	<u> </u>						
DP Scale Controls	12						
Auto-View 1	7.2						
Auto-View 2	-						
	40 -						
Saved View 1	1.0						
Saved View 2	+ +		· · · ·		1000		
Edit ranges		400	600	800	1000	1200	
	<u>~~</u>		Lime (sec.)				
x = ?, y = ?							
i=2						Data1_DP Plot1*	NUM

after "autoscaling" click 'Rescale to Show All'



titration continues



Please note that the ITC	cell status indicates	which injection is	being completed.
		2	U 1

Microcal Origin - C:\Origin50\VP1TCF	LOT.OPJ - [Plot1]		_ # X
	이 아이		
	ন		
		ITC biochian #10, 245 12 of Auglights	
Main Display	Current Status :	The Injection #10, 245.13 ul Available	
Temp (° C) 30.0	DP	Rnase112402414pm.itc	
DP(uCalisec.) 4.410	٦		
DT (° C) 0.000			
	4 - (((
	11/1/1/		
	(j 3 -) (j		
Crispray Mode			
Rescale To Show All	Dug 1		
	□ 2 -		
OP Scale Controls	-		
Auto-Mew 1		1	
Auto-View 2	'		
Saved View 1			
Count Marca 1			
saved new z	0 500	1000 1500 2000	
Edit ranges	Ne	Time (sec.)	
RO+BIOTZO.			
$\mathbf{x} = ?, \mathbf{y} = ?$			
v		Detail DP Peet*	ALM .

16. Once the titration is completed the ITC cell is thermostated and a full titration curve is displayed.

Microcal Origin - C:\Origin50\VP1TCl	PLOT.OPJ - [Plot1]		_ # ×
Ele Edit View Graph Data Anah	ysis Iools Figment Window Help		_ @ ×
8 m 🚯			
	0		
123	Current Status :	Thermostatting ITC @ 30 °C	
Main Display	0.0	Rescal12402414em its	
Temp (° C) 30.0	5 -	Rhase 1124024 14pm.tc	
DP(uCalisec.) -0.234	Ŭ		
DT (° C) 0.000			
	7.2		
Display Mode	286C		
	2 - I I I I		
Rescale To Show All			
	u 2-11111		
OP Scale Controls			
AUIO-VIEVV 1			
Auto-View 2	'-		
Saved View 1	4117		
Saved View 2		2500 3000 3500 4000 4500 5000 5500 6000 6500	
Edit ranges	→ 300 1000 1000 2000	Time (eee)	
	<u>*C</u>	Time (sec.)	
x = ?, y = ?			
			Distant Income

17. At this point the data are saved and can be processed using ORIGIN.